

## Digital clamp meters AC/DC

### PAN 600AD+ 2

Smart digital clamp meter 600 A AC / DC with automatic function selection

- Color LCD display
- Data-Hold
- Auto range
- Auto power off
- **Single-pole phase testing with acoustic alarm**
- Diode test
- **Min / Max memory**
- LED flashlight
- **temperature measurement**
- **Inrush current measurement**
- **Non contact voltage test (2 levels) (NCV)**
- **True RMS measurement**
- Indication of polarity for DC
- LCD display with bargraph 11 mm

**Scope of delivery:** test leads, Type-K temperature probe 40°C ~ 250°C, Operating manual



Technical Data	PAN 600AD+ 2
DC voltage (V=)	0,1 mV - 600 V
AC voltage (V~)	0,1 mV - 600 V
DC current (A=)	10 mA - 600 A
AC current (A~)	10 mA - 600 A
Frequency range (Hz)	10 Hz - 2 kHz
Resistance ( $\Omega$ )	0,1 $\Omega$ - 60 M $\Omega$
Continuity test (•)))	< 50 $\Omega$
Frequency (Hz)	0,01 Hz - 10 MHz
Duty-cycle	1 - 99 %
Capacitance (F)	1 pF - 60 mF
Temperature ( $^{\circ}$ C) (type K probe)	-40 - 1000 $^{\circ}$ C
Ambient temperature ( $^{\circ}$ C)	0 - 40 $^{\circ}$ C
Jaw opening $\varnothing$	26 mm
Weight (gross / net)	465,2 / 208 g
Dimensions	198 x 67 x 28 mm
Required battery(s):	3 x 1,5V AAA
Measuring category (CAT)	CAT III 600 V
Accuracy (%)	0,5 % - 5 %



PAN 600AD+ 2 Video DE:



PAN 600AD+ 2 Video EN:

